

# QC71 Single Head Water Softener Spec Sheet

**Water Requirements**

- 3/8" dedicated cold water line with shut-off valve and compression fitting.

**Shipping Dimensions & Weight**

- Height: 11 inches
- Depth: 7 inches
- Width: 10 inches
- Weight: 3 pounds

**Space Requirements**

- Height: 9 inches
- Depth: 4 inches
- Width: 6 inches
- Weight: 2 pounds

**Installation Tips**

- Choose mounting location suitable to support the full weight of the system when operating.
- Install vertically with cartridge hanging down.
- Allow 2.5" clearance below the cartridge for easy cartridge replacement.
- Flush ESO cartridge by running water through filter for five minutes at full flow.

**Operation Tips**

- Change ESO cartridge when its pre-calculated water volume has been reached.
- Do not exceed recommended service flow rate of 0.5 gpm (1.9 Lpm),
- Always flush the filter cartridge at time of installation and cartridge change.

**Water Softener/Maintenance Calculation**

Cartridge Grain Capacity	÷	Water Hardness (grains per gallon)	=	Gallon Capacity of Cartridge	÷	Gallons of Water Used per Day	=	Days Until Cartridge Needs to be Replaced
4400 gpg	÷		=		÷		=	



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation.

Customer Name: \_\_\_\_\_ Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_ Email: \_\_\_\_\_